

Dial Reading Viscometer

the original that became the world standard

The Worldwide Standard

Viscometer

Easy-to-Select Speeds

Electronic Drive

means quiet,
reliable operation

Analog display

- Shows % Torque
- Use Factor Finder to convert reading to centipoise

Simple-to-use,

easy setup

2-Year Limited Warranty

Available in explosion proof

U.L. Class 1, Division 1,
Group D locations
(w/o Electronic Drive)

Accuracy: ±1.0% of range

Repeatability: ±0.2%



Easy Speed Adjustment and On/Off Control

What's Included?

- Instrument
 - 6 spindles (RV/HA/HB) or 4 spindles (LV)
 - Spindle Guard Leg*
 - Lab Stand (Model A)
 - Carrying Case
- *Not applicable to HA or HB torque models

Optional Accessories

- Viscosity Standards
- RV/HA/HB-1 Spindle
- Quick Action Lab Stand
- Temperature Bath
- Small Sample Adapter
- UL Adapter
- Thermosel
- Spiral Adapter
- DIN Adapter
- Quick Connect/Extension Links
- Vane Spindles)

MODEL	VISCOSITY RANGE cP(mPa•s)		SPEEDS	
	Min.	Max.	RPM	Number of Increments
LVT	1†	2M	.3-60	8
RVT	100††	8M	.5-100	10
HAT	200††	16M	.5-100	10
HBT	800††	64M	.5-100	10

† 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles.
 †† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.
 M = 1 million cP = Centipoise mPa•s = Millipascal•seconds

