




# CE GROUP

## Heavy Crane Scale

| specification                            |  |   |
|--|--|---|
| model                                    | OCS-Z  | PACKING   |
| Picture                                  |    | <p>15T/20T Packages:</p>  <p>30T/50T Packages:</p>   |
| display                                  | 56mm LED   |   |
| face-board                               | 2 keys keypad  |   |
| hook                                     | American standard eye hook   |   |
| shackle                                  | American standard bow shackles   |   |
| battery                                  | 6V/4 Ah rechargeable battery   |   |
| remote controller                        | infrared remote controller   |   |
| enclosure                                | aluminum die-casting case  |   |
| function                                 | zero, tare in/out, hold/ low voltage alarm, battery supervision, overload alarm, digital calibration,tare set, total/delete/clear total, view total, resolution switch, auto off set, power-saving modedisplay luminance set, display speed set, anti-motion set, gravity acceleration set |   |
| accuracy class                           | equivalent to OIML III   |   |
| tare range                               | 100% Cap.  |   |
| Manual zero range                        | 200d   |   |
| the safety load                          | 125% F.S.  |   |
| Stability time                           | ≤5S  |   |
| The extreme limit load                   | 400% F.S.  |   |
| Continuous usage time                    | ≥40hours   |   |
| temperature range                        | -10℃~40℃   |   |
| At the expense of additional accessories |  <p>standard accessories</p>   |  <p>optional accessories</p>   |

|                  |                 |           |           |           |       |   |
|------------------|-----------------|-----------|-----------|-----------|-------|---|
| dimension        | Max Cap         | A<br>(mm) | B<br>(mm) | G<br>(mm) | N.W   |  |
|                  | 15000kg         | 93        | 142       | 1150      | 65kg  |   |
|                  | 20000kg         | 93        | 142       | 1150      | 65kg  |   |
|                  | 30000kg         | 110       | 165       | 1330      | 165kg |   |
| optional colours | red,yellow,blue |           |           |           |       |   |

| Model    | Max Capacity | Min. Capacity | Division | N.W.  | Package        |
|----------|--------------|---------------|----------|-------|----------------|
| OCS-Z-15 | 15 000kg     | 100kg         | 5/10 kg  | 70kg  | 1 wooden case  |
| OCS-Z-20 | 20 000kg     | 200kg         | 5/10 kg  | 90kg  | 1 wooden case  |
| OCS-Z-30 | 30 000kg     | 200kg         | 10 kg    | 160kg | 2 wooden cases |
| OCS-Z-50 | 50 000kg     | 400kg         | 20 kg    | 205kg | 2 wooden cases |

### OCS-Z heavy - duty electronic crane scale

- 56mm red subtitles display, visual distance  $\geq 30m$
- Auto battery voltage indication when starting / turning off
- Overload and battery low voltage alarm, to ensure the use of safety
- Use a large capacity battery, can be used for a long time
- Any weight value correction
- Show Score Value Selection
- Automatic sleep / shutdown energy saving design
- Handheld remote control, easy to operate, enhanced function

With a small cart



*Send us an email*

[sales@cegrouplb.com](mailto:sales@cegrouplb.com)



00961 1 894 243