

Lafomed LF-8L : 8 Liter Autoclave/Steam Sterilizer Class B



Fast Sterilization
Fully Automatic
8 Preset sterilization programs
Ster. Temp.: 105-134°C
Ster. Time: 4-60 min
Dry time: 1-25min
Vacuum Times: 1-10 times
B&D / Helix / Vacuum testing program
Cleaning Program
Printer & USB Output
Big Stainless Steel Water Tanks
High quality bacteria filter

Program	121°C Solid	121°C Hollow	121°C Porous	121°C Solid	121°C Hollow	121°C Porous
Vacuum Times	1	3	3	1	3	3
Temp (°C)	121	121	121	134	134	134
Pressure(KPA)	110	110	110	210	210	210
Time(Min.)	20	20	20	4	4	4
Program	Cotton	Prion	User defined	BD/Helix Test	Vacuum Test	Clean
Vacuum Times	3	3	User defined	3	1	3
Temp (°C)	134	134	User defined	134	/	105

Pressure(KPA)	210	210	User defined	210	-80	20
Time(Min.)	4	19	User defined	3.5	15	5

Model	LF-8L
-------	-------

Description	Small Autoclave
-------------	-----------------

Class	B
-------	---

Certification	CE 1023, ISO 13485
---------------	--------------------

Standard	BS EN 13060:2004 + A2:2010
----------	----------------------------

Frequency	50Hz
-----------	------

Plug	3 hole plug
------	-------------

Wattage	2.4 KW
---------	--------

Sterilization temperature	105 - 134°C
---------------------------	-------------

Max working pressure	0.21-0.23MPa
----------------------	--------------

Life span	5 years
-----------	---------

Diameter of chamber	17 CM
---------------------	-------

Depth of chamber	32 CM
------------------	-------

Volume of chamber	8 L
-------------------	-----

Material of chamber	Stainless steel 304
---------------------	---------------------

Colors available	White
------------------	-------

Screen type	LCD
-------------	-----

Screen size	6 X 4.25 cm
-------------	-------------

Language available	English, Italian, German, Chinese
Lock system of door	Mechanic + electrical lockers
User password	Yes
Output	Thermo printer & USB
Net weight	35 kgs
Gross weight / carton	42 kgs
Product size	56 X 44 X 36cm
Package size	65 X 45 X 42cm
Min size of table for installation	54 x 41.5 cm

<p><u>Warranty:</u></p> <p>Two-years warranty for whole machine Standard packing Q'ty (PCS) Autoclave 1 Power cable 1 Water drain pipe 1 Tray 3 Tray holder 1 Handle for tray holder 1 Fuse 2 Instruction manual 1</p>	<p><u>The working condition of the autoclave:</u></p> <p>* Relative humidity: ≤80% * Atmospheric pressure: >70kPa; * Voltage: 230VAC, 50Hz, 2500VA * The highest working pressure: 0.21~0.23MPa * The highest working temperature: 134~137℃</p> <p><u>The requirements of transportation and storage:</u></p> <p>* Environmental temperature range: 5~40℃ * Relative humidity: ≤80% * No corroding gases</p>
---	---

Warning:

- * Please use a 3-hole socket, and ensure the socket has been connected well with the ground. Do not put the autoclave on a place that the power are difficult to be cut off.
- * Do not use power with different voltage with which stated in this manual.
- * Do not touch the plug or socket with wet hands.
- * Do not pull, change, over-bend or twist the wires, and do not put heavy things on the wires.
- * Do not put the autoclave on an unstable table.
- * Do not block the door of autoclave, and cover the ventilation holes and radiation holes.
- * Do not put anything on the top of autoclave.
- * If you find any abnormal smell or sound during operation, please cut off the power immediately and contact your local distributor or us.