




## Watch Batteries **ENERGIZER**

### Model:362/361




DESIGNED FOR USE ON CONTINUOUS LOW DRAIN  
HIGH PULSE ON DEMAND

### Specifications

<b>Chemical System:</b>	Silver Oxide (Zn/Ag <sub>2</sub> O)
<b>Designation:</b>	IEC-SR58
<b>Nominal Voltage:</b>	1.55 Volts
<b>Typical Capacity:</b>	27 mAh* (to 1.2 volts)
<b>Capacity Test:</b>	68K ohm continuous drain at 21°C
<b>Typical Weight:</b>	0.4 grams
<b>Typical Volume:</b>	0.10 cubic centimeters
<b>Impedance (40 Hz):</b>	10 to 20 ohms

\* Varies according to the applied load, temperature, and cutoff voltage.


### Cross Section



### Typical Discharge Characteristics

Typical Performance at 21°C (70°F)

**Schedule:** Continuous  
**Typical Drain @ 1.55V:**  
0.023 milliamperes  
**Load:** 68K ohm




<u>Schedule</u>	<u>Typical Drains</u> at 1.55V (milliamperes)	<u>Load</u> (ohm)	<u>Cutoff</u> 1.2V (hours)
Continuous	0.023	68K	1,174


### Temperature Characteristics

Typical Performance at Low Discharge rates

#### Service Effects



#### Storage Effects



Made in USA