

Watch Batteries ENERGIZER Model:379



5.80 (0.228) 5.55 (0.219) R0.80 (0.031) Ref. Typical 2.15 (0.085) 1.90 (0.074) 1.95 (0.077) Ref. 1.60 (0.063) Ref. Permissible deflection from a flat 0.06 (0.002) Minimum Ref.

Specifications

Chemical System: Silver Oxide (Zn/Ag₂O)

Nominal Voltage: 1.55 Volts


Typical Capacity: 14.5 mAh* (to 1.2 volts)

Capacity Test: 68K ohm continuous drain at 21°C

Typical Weight: 0.25 grams

Typical Volume: 0.06 cubic centimeters Impedance (40 Hz): 75 to 85 ohms

* Varies according to the applied load, temperature, and cutoff voltage.




DESIGNED FOR USE ON CONTINUOUS LOW DRAIN

(applies to top edge of gasket or edge of crimp, whichever is higher)

Typical Discharge Characteristics

Typical Performance at 21°C (70°F)

Schedule: Continuous



<u>Schedule</u>	Typical Drains at 1.55V (milliamperes)	<u>Load</u> (ohm)	Cutoff 1.2V (hours)
Continuous	0.023	68K	630

Temperature Characteristics

Typical Performance at Low Discharge Rates

