



# Data Sheet





## Ultrasonic Flow Meter

PCE-TDS 100H/HS

### 3 Technical specifications of the PCE-TDS 100H/HS

<b>Model</b>	PCE-TDS 100 Series
<b>Measurement range</b>	-32 ... +32 m/s
<b>Resolution</b>	0.0001 m/s
<b>Resolution</b>	±1 % of measured value @ v >0.2 m/s
<b>Linearity</b>	0.5 % @ v >0.2 m/s
<b>Repeatability</b>	0.2 % @ v >0.2 m/s
<b>Media</b>	All liquids with an impurity of <5 % and a flow of >0.03m <sup>3</sup> /h
<b>Flow units</b>	Cubic metre [m <sup>3</sup> ] Litre [l] Gallon (USA) [gal] Imperial Gallon (UK) [igl] Million USA Gallons [mgal] Cubic foot [cf] Barrel (USA) [bal] Imperial Barrel (UK) [ib] Oil Barrel [ob] The time can be per day [/d], per hour [/h], per minute [/m] and per second [/s]
<b>Data logger</b>	1800 measuring data
<b>Interface</b>	USB (for online measurement and to read out internal memory)
<b>Protection class</b>	IP 52
<b>Power supply</b>	3 x rechargeable AA NiMH batteries / 2100 mAh (operating hours 12 h when fully charged) 100...240 V AC 50/60 H
<b>Dimensions</b>	214 x 104 x 40 mm
<b>Weight</b>	450 g

## 6 Order code PCE-TDS 100H/HS

Type of sensor	S1	M1	HS	HM
				
Order no. sensor	TDS-S1	TDS-M1	TDS-HS	TDS-HM
Order no. hand-held device + sensor	PCE-TDS 100-1	PCE-TDS 100-2	PCE-TDS 100-3	PCE-TDS 100-4
Sensor cable length	5m	5m	5m	5m
Nominal diameter	DN 15 ... DN 100 20 ... 108 mm	DN 50 ... DN 700 57 ... 720 mm	DN 15 ... DN 100 20 ... 108 mm	DN 50 ... DN 700 57 ... 720 mm
Liquid temperature	-30 ... 160 °C	-30 ... 160 °C	-30 ... 160 °C	-30 ... 160 °C
Dimensions	45 x 30 x 30 mm	60 x 45 x 45 mm	200 x 25 x 25 mm	280 x 40 x 40 mm
Weight	75 g	260 g	250 g	1080 g