## **CORDED POWER TOOLS**

## GUARANTEED TOUGH:

$\bigcirc$					
	SCREWDRIVERS	5,300 rpm <b>7</b> High Speed VSR Drywall Scrugun	4,000 rpm 7 Lightweight VSR Drywall Scrugun	4,000 rpm <b>7</b> VSR Drywall Scrugun	2,500 rpm VSR All-Purpose Scrugun
	SPECIFICATIONS	DW255	DW252	DW272/W/WT	DW257
	Amps	6.0 Amps	6.0 Amps	6.3 Amps	6.2 Amps
	No Load Speed	0 - 5,300 rpm	0 - 4,000 rpm	0 - 4,000 rpm	0 - 2,500 rpm
	Clutch	Standard	Standard	Standard	Standard
	Max Torque	60 in-Ibs	60 in-lbs	81 in-Ibs	132 in-Ibs
	Max Fastener Size	#8	#8	#8	#12
	Tool Weight	2.9 lbs	2.8 lbs	3.1 lbs	3.5 lbs
	Includes	-	-	W = 50'  cord WT = 50'  twist lock cord	-
$\bigcirc$					
		2,500 rpm Heavy-Duty VSR All-Purpose Scrugun	2,500 rpm VSR Depth-Sensitive TEKS® Scrugun	2,500 rpm Lightweight VSR All-Purpose Scrugun Kit	2,000 rpm VSR VERSA-CLUTCH™ Scrugun
	SPECIFICATIONS	DW276	DW266	DW260K	DW267
	Amps	6.5 Amps	6.5 Amps	6.2 Amps	6.5 Amps
$\bigcirc$	No Load Speed	0 - 2,500 rpm	0 - 2,500 rpm	0 - 2,500 rpm	0 - 2,000 rpm
	Clutch	Standard	Standard	Standard	VERSA-CLUTCH <sup>™</sup> System
$\smile$	Max Torque	132 in-lbs	132 in-lbs	132 in-lbs	164 in-Ibs
	Max Fastener Size	#14	#14	#12	#14
	Tool Weight Includes	3.6 lbs	3.5 lbs	3.2 lbs 1/4", 5/16", 3/8" Nut setters,	3.7 lbs
	linciudes	-	-	3 locators	-
$\bigcirc$					
$\smile$		2,500 rpm	1,000 rpm	2,500 rpm 🛿 VSR Positive-Clutch Scrugun with 1/4" Bit Holder	2,500 rpm VSR Positive-Clutch Scrugun with Threaded Clutch Housing
	SPECIFICATIONS	DW268	DW269	DW281	DW284
	Amps	6.5 Amps	6.5 Amps	6.5 Amps	6.5 Amps
	No Load Speed	0 - 2,500 rpm	0 - 1,000 rpm	0 - 2,500 rpm	0 - 2,500 rpm
	Clutch	VERSA-CLUTCH™ System	VERSA-CLUTCH™ System	Positive	Positive
	Max Torque Max Fastener Size	132 in-lbs #14	344 in-lbs #14	132 in-lbs	132 in-lbs
	Max Fastener Size	#14	#14	#14	#14
	Tool Weight	3.7 lbs	3.7 lbs	3.4 lbs	3.3 lbs



TEKS® is a registered trademark of Illinois Tool Works, Inc.