



Technical Data

Power 85-265V- 50/60Hz - DC 12V 1000mA	Units g oz lb ct N ozt
Capacity 120g 220g 220g 320g 520g	Repeatability Error +/- 1d
Accuracy 0.1mg 1mg	Calibration BAE- External BAE*C- Internal
Display TFT	Output RS232
Pan Size Dia 90mm	Weight 5.5kg

TFT TouchScreen

- Professional design with touch screen
- Eye-friendly Metro color interface design
- Sensitive touch panel, work even with gloves
- Easy for operating with a lot indicating messages
- Multi functions: counting, percentage, density, etc.
- RS232 interface for connecting with computer or printer
- High-transparent glasses, with lock for transportation
- Stainless steel weighing pan with wind shield kit
- Stainless steel bubble level and adjusting feet
- Special designed overloading protection for the sensor
- Multi-units exchange: g/oz/lb/ct/N/ozt
- Big capacity up to 520g
- High precision up to 0.1mg
- Internal or External calibration
- Optional USB interface
- Optional density weighing kit

Accessories

- Statistics printer - XT110
- Label printer - T40
- Balance Table I - 900 x 600mm
- Balance Table II - 1200 x 600mm

Models

Part No.	101101	101102	101103	101104	101105
Models	BAE124	BAE224	BAE223	BAE323	BAE523
Part No.	101106	101107	101108	101109	101110
Models	BAE124C	BAE224C	BAE223C	BAE323C	BAE523C
Capacity	120g	220g	220g	320g	520g
Division	0.1mg	0.1mg	1mg	1mg	1mg
S.S Pan			Dia 90mm		
Weight			5.5kg 6kg		