

## SW Waterproof Weighing Scales

### General Specifications

• Display	25mm digit LCD display, with white LED backlight
• Capacities	3kg~30kg
• Platform size	200 x 260mm
• Keyboard	3keys(Mechanical switch)
• Housing	ABS plastic
• Max. Divisions	3,000e; 2x3,000e; 6,000d
• ADC update	≤ 1/10 second
• Operate Temp	-10°C~+40°C
• Power	AC adapter (12V/500mA), internal rechargeable battery (6V/3.2Ah)
• Gross weight	2.78kg
• Packing	Master carton 4 in 1, dimension 0.118m <sup>3</sup> , 40 feet container can load 1840machine, 20 feet container can load 920 machine



- IP65 waterproof housing design
- Selectable weighing units
- With hand breathable knob design
- OIML approval from Delta(approval no.:DK0199.255)
- Battery provide up to 70 hours of continuous use(without backlight)
- Optional 15mm rear display
- Optional initial-verification



## SW Waterproof Weighing Scales

Model Name	Capacity	Readability	Division	Approx. weight	Approval
SW-3K	3kg	0.5g	6,000d	2.78kg	CE
SW-6K	6kg	1g	6,000d	2.78kg	CE
SW-15K	15kg	2g	6,000d	2.78kg	CE
SW-30K	30kg	5g	6,000d	2.78kg	CE
SW-3K-M	3kg	1g	3,000e	2.78kg	CE, OIML
SW-6K-M	6kg	2g	3,000e	2.78kg	CE, OIML
SW-15K-M	15kg	5g	3,000e	2.78kg	CE, OIML
SW-30K-M	30kg	10g	3,000e	2.78kg	CE, OIML
SW-6K-MR	6kg	1g/2g	2x3,000e	2.78kg	CE, OIML
SW-15K-MR	15kg	2g/5g	2x3,000e	2.78kg	CE, OIML
SW-30K-MR	30kg	5g/10g	2x3,000e	2.78kg	CE, OIML

### Options



### Dimensions(mm)

